

4000016715

P-5111

Desk Mount Telephone



DESCRIPTION

- Watertight IP-65
- Strong call tone ≥ 95 db (A), 1m
- Shock resistant housing
- Complies with IEC 60945 Standard for Marine Equipment
- DNV-GL type approval

The P-5111 is a desk or wall mounted watertight analog telephone for industrial and exposed environments.

SPECIFICATIONS

MECHANICAL

Dimensions (WxHxD)	191x317x128 mm
Weight	2.3 kg
Material	Polycarbonate
Color	RAL 9005
Mounting	Desk / Wall
Fixing	4 x M6 bolts
Access	Front
Cable Entry	Bottom
Gland Type	1 x M20, 1 x M20 blind plug, 2 x M12 blind plug

ELECTRICAL

Power Supply	Telephone line (self-contained)
Telephone line feed voltage	24-64 VDC
Ring Voltage / Frequency	30 < R < 90V / 16 < F < 68 Hz
Dial Method	PD (1.5:1 (60/40ms) or 2:1 (66.7/33.3ms)) / DTMF (ITU-T Q23)
Ringing Volume	≥ 95 dB(A) at 1 m distance
Termination	Screw terminals ≤1.5 mm ²

ENVIRONMENTAL

Temperature	-25°C to +55°C (Storage: -30°C to +70°C)
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-65

TECHNICAL DIMENSIONS

