

4000200200

P-7210

Desktop/Wall VoIP Telephone



DESCRIPTION

- Integrated loudspeaker / microphone
- Handset, 2-meter sturdy curled cord
- Hands-free, duplex communication
- 2" Graphic backlit display:
 - Menus and navigation wheel/key
 - Contact list
 - Caller ID
- Dimmable backlight (keypad)
- Privacy switch (Do not disturb) with priority override
- Manual PTT (push-to-talk) key
- 3 pcs programmable direct access keys (A-B-C)
- Volume adjustment with override
- Speakerphone SPL level >85dB(A)
- Desk or bulkhead mounted
- MMI according to IEC 62288 Ed 2.0
- Status/health indicator
- Multiple ring melodies
- 2-port 100Mbit Ethernet switch for data connectivity
- Complies with IEC 60945 Standard for Marine Equipment
- DNV/ABS/RMRS/CCS type approval and compatible with NORSOK

The P-7210 Telephone is an indoor accommodation unit, normally used in cabins, offices, etc. This is a VoIP station with handset, loudspeaker, internal microphone, memory functions and more. The unit can be desk or bulkhead mounted.

Created: 11.12.2019, updated: 17.01.2020

page 1/3

www.zenitel.com

info@zenitel.com

Zenitel and its subsidiaries assume no responsibility for any errors that may appear in this publication, or for damages arising from the information therein. Vingtor-Stentofon products are developed and marketed by Zenitel. The company's Quality Assurance System is certified to meet the requirements in NS-EN ISO 9001. Zenitel reserves the right to modify designs and alter specifications without notice.

ZENITEL PROPRIETARY. This document and its supplementing elements, contain Zenitel or third party information which is proprietary and confidential. Any disclosure, copying, distribution or use is prohibited, if not otherwise explicitly agreed in writing with Zenitel. Any authorized reproduction, in part or in whole, must include this legend. Zenitel - All rights reserved.

SPECIFICATIONS

MECHANICAL

Dimensions (WxHxD)	144 x 216 x 95.5 mm
Weight	0.9 kg
Material	Plastic (PC/ASA)
Color	Grey – RAL 7021/7043
Mounting	Table / Wall with wall contact
Fixing	Bulkhead: 2 x M4 bolts
Access	Front
Cable Entry	Rear
Connector Type	RJ45 (line) / RJ12 (headset)

ELECTRICAL

Power Supply	PoE / 24VDC (Optional external power)
Line Format	VoIP, PoE
Power Consumption	3 W (max)
Termination	RJ45
Compass Safe Distance	>5 m

ENVIRONMENTAL

Temperature	-15°C to +55°C
Humidity	+93% (at +40°C)
Ingress Protection Rating	IP-22 (protected environment)
UL94	V0

TECHNICAL DIMENSIONS

